

ACCOGRAISSE LITHIUM MULTI



400g | 900g | 5Kg | 25Kg | 50Kg | 180 Kg

Grease

High quality grease for multiple use, particularly for **the car, industry, and civil engineering.**

Type of use : moderately loaded bearings, sliding channel, textile machine under moderate load and high speed until 3000 revs/mn ; general lubricating of tractors, trailer, hubs of civil engineering machine ; articulations, universal joints, pumps, ...

NLGI 2

«Extreme pressure» properties

Wear components in movement reduced.

Very good sticking

Excellent quality in service.

Very good lubricating power

Technical data

Nature of the soap : lithium

Color : amber

Appearance : smooth

Penetration [NF T 60-132] (1/10mm) : 265/285

Limit temperature of use (°C) : -20 to +140

4 weld balls [ASTM D 2596] (Kg) : 200

4 wear balls 1h/40kg [ASTM D 2266] (mm) : 0.70

Corrosion Cu 3 h/100°C [ASTM D 4048] (b) : 1

Oxidation after 100 h [ASTM D 942] (psi) : < 7

EMCOR Test distilled water [NF T 60-135] : 1

Wash out [ASTM D 1264] at 80°C (% weight) : < 4

Wheel bearing [ASTM D 1263] at 105°C : 1

The given data are typical data.