

## ACCOFARM TP 10W-40

Multi-purpose oil  
Semi-synthetic

High performance multi-purpose oil developed for the lubrication of all major components of tractors and civil engineering equipment: engines, wet brakes, transmission and hydraulic systems.  
It can also lubricates fixed compressors in building sites.

### SPECIFICATIONS

API CG4/CE/SF

API GL4 - GL5 (high torque - low speed)

DIN 51506 VCL

FNH 8200920 : 1/2/3

FORD M2C 159B

JOHN DEERE DM J27

MASSEY FERGUSSON M1139/1144

MT-1 MIL.L. 2104D

### TECHNICAL DATA

Viscosity at 40°C (cSt)	89.8
-------------------------	------

Viscosity at 100°C (cSt)	13.6
--------------------------	------

Viscosity Index	153
-----------------	-----

Density at 20°C	0.873
-----------------	-------

Viscosity at -25°C (cP)	6240
-------------------------	------

*The given data are typical data.*

### PACKAGING

> 30L – 125785

> 60L – 125786

> 220L – 125789

### PROPERTIES

Friction modifying additive → Jamming effects prevented

Detergent, dispersant, anticorrosion, → Avoid deposits, varnishes and ring sticking

extreme pressure properties → Excellent filterability

Direct download: <https://accor-lubrifiants.com/EN/ft/12578.pdf>