Last edition: 15/05/2023

Please regularly check that you have the latest up-to-date technical data sheet

COUPE LS 120

Metal working oil
Semi-synthetic

Soluble cutting designed for metal working : turning, milling, drilling, sawing, cutting, boring, threading, screw cutting. It is formulated with corrosion inhibitors and efficient bactericides.
This product is used diluted by 4 to 6% in water according to work conditions.

SPECIFICATIONS

ISO - L - MAH

PACKAGING

> 30L – 126205

TECHNICAL DATA

Biostable product	
Color	Clear, amber
Density at 20°C	0.99
pH-value 30 vol. %	9.5
Corrosion test Herbert (IP 125)	0/0-0
Foaming test IP 312	initial/5 mn (mml) : 30/0
Maximum temperature for storage	> 0°C

Take precautions when used with non ferrous metals, particularly with copper and aluminium.

The given data are typical data.

PROPERTIES

Resistant to bacterial attacks

Antiwear and anticorrosion properties

Haut pouvoir High cooling power

No gumming of the sliding channels

Easily miscible with water, quick formation (without heating) of a clear and very stable micro-emulsion

Direct download: https://accor-lubrifiants.com/EN/ft/12620.pdf

ACCOR lubrifiants, 8 rue du Mans Z.I. de la Dabardière BP 30406 - 49304 Cholet Cedex - France
Tel +33 (0)2 41 75 26 70 - Fax +33 (0)2 41 62 67 02 - www.accor-lubrifiants.com
SAS au capital de 450 000 € n° siret 328 666 391 00029 code APE 1920 Z